

**GULFSTAR 4T THRILLER**  
Two Wheeler Oil

**Typical Characteristics**

| SI No | TESTS             | TEST METHOD    | UNIT               | SPECIFICATION BY OLG |
|-------|-------------------|----------------|--------------------|----------------------|
|       |                   |                |                    | SAE 20W-40           |
| 1     | Appearance        | Visual         | Visual Examination | Clear Transparent    |
| 2     | Colour            | ASTM D 1500    | NO                 | ASTM 3.0 MAX         |
| 3     | Density at 29.5°C | ASTM D 1298    | gram/ml            | 0.880-0.885          |
| 4     | Viscosity @ 40 °C | ASTM D 445     | cSt                | 125-135              |
| 5     | Viscosity @100 °C | ASTM D 445     | cSt                | 14.5-15.0            |
| 6     | Viscosity Index   | ASTM D 2270    | NO                 | 115 MIN              |
| 7     | CCS viscosity     | ASTM D 5293    | CP                 | <9500 cP at -15°C    |
| 8     | Pour point        | ASTM D 97      | °C                 | -24                  |
| 9     | Flashpoint        | ASTM D 92 & 93 | °C                 | 230 °C               |
| 10    | Total Base number | ASTM D 2896    | mg.KOH/gm          | 6.08                 |
| 11    | Foaming Character | ASTM D 892     | SEQUENCE I, MI     | 10 ML/5 ML           |
|       |                   |                | SEQUENCE II, MI    | 20 ML/10 ML          |
|       |                   |                | SEQUENCE III, MI   | 10 ML/5 ML           |
| 12    | Sulfated ASH%     | ASTM D 874     | BY WT%             | 1.1                  |