

**GULFSTAR ATF DEX III**  
**Automatic Transmission Oil**

**Typical Characteristics**

| SI No | TESTS                                   | TEST METHODS   | UNITS              | SPECIFICATION BY ORYX<br>GULFSTAR ATF DEXO III |
|-------|-----------------------------------------|----------------|--------------------|------------------------------------------------|
|       |                                         |                |                    | DEXRON III-H                                   |
| 1     | Appearance                              | Visual         | Visual Examination | Clear Transparent                              |
| 2     | Colour                                  | ASTM D 1500    | NO                 | Red                                            |
| 3     | Viscosity @ 40 °C                       | ASTM D 445     | cSt                | 40                                             |
| 4     | Viscosity @100 °C                       | ASTM D 445     | cSt                | 7.0-7.5                                        |
| 5     | Viscosity Index                         | ASTM D 2270    | NO                 | 130 min                                        |
| 6     | Brookefield Dynamic Viscosity @ - 40 °C | ASTM D 2983    | cP                 | 20 000 cP Max                                  |
| 7     | Pour point                              | ASTM D 97      | 0c                 | -42                                            |
| 8     | Flashpoint                              | ASTM D 92 & 93 | 0c                 | 210                                            |
| 9     | Foaming Character                       | ASTM D 892     | SEQUENCE I, MI     | 0 ML/ 0 ML                                     |
|       |                                         |                | SEQUENCE II, MI    | 0 ML/ 0 ML                                     |
|       |                                         |                | SEQUENCE III, MI   | 0 ML/ 0 ML                                     |
| 10    | Sulfated ASH%                           | ASTM D 874     | BY WT%             | 0.5                                            |